



Photo © Textron Aviation Inc.

GOODRICH® DE-ICE BOOTS FOR BEECHCRAFT KING AIR®

UNMATCHED EXPERTISE IN DE-ICING

Available for 90, 100, 200, 300 and 350 Series

- Your choice of installation methods – Collins Goodrich® FASTboot® or standard
- System performance optimized in the Goodrich icing wind tunnel and rain erosion silo
- Same-day shipping available
- Industry-leading five-year/3,000 flight hour warranty*

*For full warranty terms, see the Collins Goodrich RPL catalog.

For additional Goodrich
product information:

800.DE-ICERS (800.334.2377)
dssd.support@collins.com

collinsaerospace.com/deicing

Distributed by:

Beechcraft



Hawker

TEXTRON AVIATION

parts.txtav.com

To place an order or to contact your regional support team,
please visit our website.



Collins Aerospace

BEECHCRAFT KING AIR 90 SERIES

GOODRICH P/N	DESCRIPTION	WT. (lbs.)	B90 S./	B90 S./	C90 S/N	C90 S/N	C90 S/N	C90 S/N	C90 S/N	C90A/B/GT/GtI/GTx	E90 S/N	E90 S/N	F90, F90-1
			LJ-318 THRU LJ-376	LJ-318 THRU LJ-501	LJ-502 THRU LJ-577 (WITH LIGHTS)	LJ-624 (WITHOUT LIGHTS)	LJ-639	LJ-658	LJ-1062	LJ-1062	(KING AIR)	LW-119	LW-120 UP
5E1319	ENGINE INLET ANTI-ICER		2	2	2	2	2	2	2			2	
23S-2014-10-1	VERTICAL STABILIZER DE-ICE BOOT	2.1	1	1	1	1	1	1	1			1	
23S-2014-11-1	BREAK-LIGHT LH DE-ICE BOOT	6.6	1	1	1								
23S-2014-11-2	BREAK-LIGHT RH DE-ICE BOOT	6.6	1	1	1								
23S-2014-12-1	LIGHT-TIP LH DE-ICE BOOT	1.2	1										
23S-2014-12-2	LIGHT-TIP RH DE-ICE BOOT	1.2	1										
23S-2014-9-1	HORIZONTAL STABILIZER LH/RH DE-ICE BOOT	2.9	2	2	2	2	2	2			2		
23S-2014-15-1	LIGHT-TIP LH DE-ICE BOOT	1.0		1	1						1		
23S-2014-15-2	LIGHT-TIP RH DE-ICE BOOT	1.0		1	1						1		
23S-2014-20-1	WING LH DE-ICE BOOT	7.0				1							
23S-2014-20-2	WING RH DE-ICE BOOT	7.0			1								
23S-2014-21-1	WING LH DE-ICE BOOT	7.0					1				1		
23S-2014-21-2	WING RH DE-ICE BOOT	7.0					1				1		
25S-7D5064-05	HORIZONTAL STABILIZER LH/ RH DE-ICE BOOT	2.0						2	2	2		2	
25S-7D5064-10	VERTICAL STABILIZER DE-ICE BOOT	1.5						1	1	1		1	
25S-7D5064-25	WING LH DE-ICE BOOT (REPLACES 25S-7D5064-03)	6.0						1	1	1	1		
25S-7D5064-26	WING RH DE-ICE BOOT (REPLACES 25S-7D5064-04)	6.0						1	1	1	1		
P25S-7D5064-05	FASTBOOT® HORIZONTAL STABILIZER LH/ RH DE-ICE BOOT	2.0						2	2	2		2	
P25S-7D5064-10	FASTBOOT® VERTICAL STABILIZER DE-ICE BOOT	1.5						1	1	1		1	
P25S-7D5064-25	FASTBOOT® WING LH DE-ICE BOOT (REPLACES P25S-7D5064-03)	6.0						1	1	1	1		
P25S-7D5064-26	FASTBOOT® WING RH DE-ICE BOOT (REPLACES P25S-7D5064-03)	6.0						1	1	1	1		
25S-7D5064-03	WING LH DE-ICE BOOT	6.0										1	
25S-7D5064-04	WING RH DE-ICE BOOT	6.0										1	
P25S-7D5064-03	FASTBOOT® WING LH DE-ICE BOOT	6.0										1	
P25S-7D5064-04	FASTBOOT® WING RH DE-ICE BOOT	6.0										1	
25S-7D5064-01	WING LH DE-ICE BOOT	5.1											1
25S-7D5064-02	WING RH DE-ICE BOOT	5.1											1
25S-7D5064-17	HORIZONTAL STABILIZER LH DE-ICE BOOT	3.6											1
25S-7D5064-18	HORIZONTAL STABILIZER RH DE-ICE BOOT	3.6											1
P25S-7D5064-01	FASTBOOT® WING LH DE-ICE BOOT	5.1											1
P25S-7D5064-02	FASTBOOT® WING RH DE-ICE BOOT	5.1											1
P25S-7D5064-17	FASTBOOT® HORIZONTAL STABILIZER LH DE-ICE BOOT	3.6											1
P25S-7D5064-18	FASTBOOT® HORIZONTAL STABILIZER RH DE-ICE BOOT	3.6											1
74-451-11	A-56-BR-1 CONDUCTIVE EDGE SEALER (1/2 PINT)		3	3	3	3	3	3	3	3	3	3	3
PR1422	FILLERS (AMM CALLS OUT PR-1422 WITH ALTERNATES)		1	1	1	1	1	1	1	1	1	1	1
PR1425	FILLERS (AMM CALLS OUT PR-1425 WITH ALTERNATES)		1	1	1	1	1	1	1	1	1	1	1
130421-011-00	STALL STRIP (2 REQUIRED)												2
130421-009-00	STALL STRIP (2 REQUIRED)		2	2	2	2	2	2	2	2	2	2	2
PR1829	ADHESIVE (AMM CALLS OUT PR-1829 WITH ALTERNATES)		1	1	1	1	1	1	1	1	1	1	1
74-451-207	FASTBOOT® PRIMER (1/2 PINT) (3-COAT APPLICATION)							8	8	8		8	8
1300L	NEOPRENE HIGH PERFORMANCE RUBBER AND GASKET ADHESIVE		1	1	1	1	1	1	1	1	1	1	1
	PEERCO #321 ADHESIVE REMOVER (AS NEEDED)												
	TOLUENE (SOLVENT) (AS NEEDED)												

For detailed installation instructions, refer to Goodrich manual 30-10-31 or FASTboot installation instructions 30-10-70.

BEECHCRAFT KING AIR 100 SERIES, SUPER KING AIR 200/300/350 SERIES

GOODRICH P/N	DESCRIPTION	WT. (lbs.)	100	A100	A100A, A100C	B100	200s	RAISBECK CONVERSION 200s	300, 300LW	B300, B300C	350s
23S-2014-11-1	BREAK-LIGHT LH DE-ICE BOOT	6.6	1								
23S-2014-11-2	BREAK-LIGHT RH DE-ICE BOOT	6.6	1								
23S-2128-5-1	HORIZONTAL STABILIZER LH/RH DE-ICE BOOT	4.4	2								
23S-2128-6-1	VERTICAL STABILIZER DE-ICE BOOT	3.1	1								
5E1319	ENGINE INLET ANTI-ICER		2	2	2						
25S-7D5064-01	WING LH DE-ICE BOOT	5.1		1		1					
25S-7D5064-02	WING RH DE-ICE BOOT	5.1		1		1					
25S-7D5064-07	HORIZONTAL STABILIZER LH/RH DE-ICE BOOT	3.1		2		2					
25S-7D5064-23	VERTICAL STABILIZER DE-ICE BOOT	2.2		1		1					
P25S-7D5064-01	FASTBOOT* WING LH DE-ICE BOOT	5.1		1		1					
P25S-7D5064-02	FASTBOOT* WING RH DE-ICE BOOT	5.1		1		1					
P25S-7D5064-07	FASTBOOT* HORIZONTAL STABILIZER LH/RH DE-ICE BOOT	3.1		2		2					
P25S-7D5064-23	FASTBOOT* VERTICAL STABILIZER DE-ICE BOOT	2.2		1		1					
25S-7D5041-01	OUTBOARD WING LH DE-ICE BOOT	6.2					1	1			
25S-7D5041-02	OUTBOARD WING RH DE-ICE BOOT	6.2					1	1			
25S-7D5041-05	HORIZONTAL STABILIZER LH/ RH DE-ICE BOOT	2.8					2	2			
25S-7D5041-07	INBOARD WING LH DE-ICE BOOT	1.6					1				
25S-7D5041-08	INBOARD WING RH DE-ICE BOOT	1.6					1				
P25S-7D5041-01	FASTBOOT* OUTBOARD WING LH DE-ICE BOOT	6.2					1	1			
P25S-7D5041-02	FASTBOOT* OUTBOARD WING RH DE-ICE BOOT	6.2					1	1			
P25S-7D5041-05	FASTBOOT* HORIZONTAL STABILIZER LH/RH DE-ICE BOOT	2.8					2	2			
P25S-7D5041-07	FASTBOOT* INBOARD WING LH DE-ICE BOOT	1.6					1				
P25S-7D5041-08	FASTBOOT* INBOARD WING RH DE-ICE BOOT	1.6					1				
25S-7D5041-13	INBOARD WING LH DE-ICE BOOT	1.5						1			
25S-7D5041-14	INBOARD WING RH DE-ICE BOOT	1.5						1			
25S-7D5041-09	INBOARD WING LH DE-ICE BOOT	1.3							1	1	1
25S-7D5041-10	INBOARD WING RH DE-ICE BOOT	1.3							1	1	1
25S-7D5041-11	OUTBOARD WING LH DE-ICE BOOT	6.2							1		
25S-7D5041-12	OUTBOARD WING RH DE-ICE BOOT	6.2							1		
25S-7D5064-17	HORIZONTAL STABILIZER LH DE-ICE BOOT	3.6							1	1	1
25S-7D5064-18	HORIZONTAL STABILIZER RH DE-ICE BOOT	3.6							1	1	1
P25S-7D5041-09	FASTBOOT* INBOARD WING LH DE-ICE BOOT	1.3							1	1	1
P25S-7D5041-10	FASTBOOT* INBOARD WING RH DE-ICE BOOT	1.3							1	1	1
P25S-7D5041-11	FASTBOOT* OUTBOARD WING LH DE-ICE BOOT	6.2							1		
P25S-7D5041-12	FASTBOOT* OUTBOARD WING RH DE-ICE BOOT	6.2							1		
P25S-7D5064-17	FASTBOOT* HORIZONTAL STABILIZER LH DE-ICE BOOT	3.6							1	1	1
P25S-7D5064-18	FASTBOOT* HORIZONTAL STABILIZER RH DE-ICE BOOT	3.6							1	1	1
25S-7D5041-17	OUTBOARD WING LH DE-ICE BOOT	6.4								1	1
25S-7D5041-18	OUTBOARD WING RH DE-ICE BOOT	6.4								1	1
P25S-7D5041-17	FASTBOOT* OUTBOARD WING LH DE-ICE BOOT	6.4								1	1
P25S-7D5041-18	FASTBOOT* OUTBOARD WING RH DE-ICE BOOT	6.4								1	1
74-451-11	A-56-BR-1 CONDUCTIVE EDGE SEALER (1/2 PINT)		3	3		3	4	4	4	4	4
PR1422	FILLERS (AMM CALLS OUT PR-1422 WITH ALTERNATES)		1	1		1	1	1	1	1	1
PR1425	FILLERS (AMM CALLS OUT PR-1425 WITH ALTERNATES)		1	1		1	1	1	1	1	1
130421-011-00	STALL STRIP (2 REQUIRED)						2	2	2	2	2
130421-009-00	STALL STRIP (2 REQUIRED)		2	2		2					
PR1829	ADHESIVE (AMM CALLS OUT PR-1829 WITH ALTERNATES)		1	1		1	1	1	1	1	1
74-451-207	FASTBOOT* PRIMER (1/2 PINT)			9		9	7	6	13	11	11
1300L	NEOPRENE HIGH PERFORMANCE RUBBER AND GASKET ADHESIVE		1	1	1	1	1	1	1	1	1
	PEERCO #321 ADHESIVE REMOVER (AS NEEDED)										
	TOLUENE (SOLVENT) (AS NEEDED)										

For detailed installation instructions, refer to Goodrich manual 30-10-31 or FASTboot installation instructions 30-10-70.

DE-ICE BOOT CARE PRODUCTS



**COLLINS GOODRICH®
AEROSPACE PROTECTANT™**

Aerospace Protectant (32 fl. oz.)
P/N 74-451-237-12

- Approved for use on all Goodrich de-icers
- Near 100% prevention of UV-caused slow fade
- Resistance to dust, soiling and staining
- Water-based formula is environmentally friendly
- Apply as needed – no surface stripping required



**COLLINS GOODRICH®
AEROSPACE CLEANER™**

Aerospace Cleaner (32 fl. oz.)
P/N 74-451-238-32

- Approved for use on all Goodrich de-icers
- Can be used on all water-safe materials
- Water-based formula is environmentally friendly
- Apply as needed – no surface stripping required
- Great for removing dirt, grime and bugs



AGE MASTER® #1

P/N 74-451-127

- Rubber preservative that protects against weathering, ozone and ultraviolet rays
- Apply six months after new de-icer is installed
- Reapply every 150 flight hours (twice yearly)
- One quart covers approximately 90 sq. ft. (8.3 sq. m)



**COLLINS GOODRICH®
ICEX®II**

ICEXII – 6 oz.
ICEXII – Pump
ICEXII – Quart

- Ice adhesion inhibitor that enhances de-icer performance
- Apply every 50 flight hours during icing season
- One quart covers approximately 400 sq. ft. (37 sq. m)



**COLLINS GOODRICH®
SHINEMASTER™
DE-ICER TREATMENT**

ShineMaster Prep
P/N 74-451-179
ShineMaster
P/N 74-451-178

- Cosmetic coating that provides a high luster shine
- Clean de-icer with ShineMaster Prep before applying 2-3 light coats
- One pint covers approximately 200 sq. ft. (18.6 sq. m)
- Reapply as desired



**COLLINS GOODRICH®
EDGE SEALER**

Edge Sealer (1/2 pint)
P/N 74-451-11
Edge Sealer (quart)
P/N 74-451-11-1

- Formulated for cosmetic appearance and static dissipation
- Kits are the same for standard and FASTboot neoprene de-icers



**PINHOLE
REPAIR KIT**

P/N 74-451-AE

- Repairs can be made on pinholes that do not exceed 1/16" diameter
- No more than 20 repairs per 12" square



**PATCH
REPAIR KIT**

P/N 74-451-AA

- Extend the life of your de-icer with a permanent patch repair

Specifications subject to change without notice.

Collins Aerospace is solely responsible for the information contained herein.

**For additional Goodrich
product information:**

800.DE-ICERS (800.334.2377)
dssd.support@collins.com

Distributed by:

Beechcraft

Cessna

Hawker

TEXTRON AVIATION

parts.txtav.com

To place an order or to contact your regional support team,
please visit our website.



Collins Aerospace

800.DE-ICERS (800.334.2377)

dssd.support@collins.com

collinsaerospace.com/deicing